FALIZ
PAJOUHESH PARS CO.

FALIZ PAJOUHESH PARS CO.



F12.B13

TUBING SWAGE

Tubing swages are used to swage out mashed or lightly collapsed tubing areas and other obstructions in the tubing string to ensure free passage of the subsurface devices.

* It is sometimes used to open “orange peel” type bull plugs on the lower end of the tubing. Tubing swages have a top threaded connection, fishneck and is tapered at both ends.
* Since the waist of the tool is approximately equal to the drift diameter of the tubing, fluid bypass is provided by a central bore and lateral ports.
* The swage O.D. should be matched to the tubing drift I.D. of the size being run.
* It should always be run on the bottom of an up-stroke (upward jarring) jar so that it can be worked free if it becomes jammed in the restriction.
* Manufactured from high-strength alloy steel to withstand repeated jarring impact without deforming, and available with a tapered nose profile suited to the restriction being cleared.

Size:

1.25" – 1.50" | 1.50" – 2.00" | 2.00" – 2.50" | 2.50" – 3.00" | 3.00" – 4.00" | 4.00" – 5.00" | 5.00" – 6.00"

No.721, phase 2, Industrial zone 2 Andimeshk Road, Ahvaz, Khuzestan
www.falizgroup.co info@falizgroup.co
061-33739164-7 061-33739163 09163001892-09168089194