FALIZ PAJOUHESH PARS CO.



F3.C3

Truck Mounted Cementing Unit

This is a double pump cementing unit equipped with plunger triplex pumps that is new generation of truck mounted cementing unit. The high energy mixing system and other hydraulic equipment is powered by the transmissions PTOs. This unit is mainly utilized for cementing, acidizing, pressure testing and other fluid pumping jobs, with configuration of 6x4 or 6X6 chassis.

Dimensions & Weights

[L] 11.3 m [W] 2.6 m [H] 4.2 m [Weight] 30000 kg

Technical Specification

Max. working pressure: 14000 psi (with 4” fluid end of TPH400 pump)
Max. flow rate: 17.2 BPM (with 4.5”+4” fluid end TPH400 pump)
Density range: 1.3 ~ 2.5 g/cm³
Mixing capacity: 0.3 ~ 2.3 m³/min
Working ambient temperature: -20°C ~ +55°C
Displacement tank capacity: 20 bbl (2x10 bbl)
Mixing tank capacity: 8 bbl

Main Equipment

* Diesel engines: 2x Caterpillar C13 475 HP @ 2100 rpm; 2x Caterpillar C15 540 HP (optional); 2x Detroit Diesel S60 600 HP (optional); 2x OM502LA 600 HP (optional)
* Transmission: 2x Allison 4700 OFS; 2x ZF TC Tronic (optional)
* Triplex Plunger pump: 2x Serva TPH400 [4” & 4.5” fluid end]; optional TPD600 / WET-TWS600
* Centrifugal pumps: 2x Serva 6x5x11 (Recirculation & Boost); 1x Serva 4x3x13 (Mix water); optional NOV Magnum Mission / Abran Sanat
* Densitometer: 1x Emerson Micromotion F300 (Non-radioactive)
* Mixer: 1x High energy mixing injector

Features

* High energy recirculation jet mixing system
* Off-center dry cement valve avoids bulk cement from chocking
* Emergency shutdown system of air inlet shut off
* Plunger pump over pressure mechanical protection system
* Plunger pump over pressure electronic protection system
* Simplify operation, adapts to working habits in oilfield
* PLC-based control system with 12” operation screen
* Level indicator & level transmitter for displacement / mixing tank
* Barrel counter for displacement tank
* Sight glass for fuel tank, hydraulic oil reservoir and lubrication tank
* Stainless steel control panel with engraved words in english
* PTO driven hydraulic system (PTO of transmissions)
* Air actuated butterfly valves
* High pressure manifold 15000 psi
* Turbine flowmeters for water & slurry
* 15000 psi Protector meters & 6” dial gauges for pressure indicating system
* Hydraulic oil cooler with electrical fan

Note

Layout of equipment is variable according to type of selected plunger pumps.

No.721, phase 2, Industrial zone 2 Andimeshk Road, Ahvaz, Khuzestan
www.falizgroup.com info@falizgroup.com
061-33739164-7 061-33739163 09163001892-09168089194